

Stucco Italiano



STUCCO DELIGHT

DESCRIPTION

Stucco Delight is a 100% solids epoxy floor coating system. It includes additives that create an evolving drift dynamic in this extraordinary floor coating system. Stucco Delight is a decorative, durable, mar and chemical resistant coating, available in a high gloss finish.

USES

Stucco Delight is designed for use in hotels, casinos, showrooms, salons, restaurants, and residential floors. Stucco Delight is designed to be used on interior floors when a truly unique floor coating is desired.

ADVANTAGES

- Decorative
- High Build
- Durable
- Seamless
- Unique Effects
- Variety of Colors
- Chemical Resistant

PACKAGING

Stucco Delight Part A – 667grams
Stucco Delight Part B – 333grams

INSPECTION

Concrete must be clean, dry, and free of grease, paint, oil, dust, curing agents, or any foreign material that will prevent proper adhesion. The concrete should be at least 20MPa and preferably a wood float finish. The concrete should be porous and able to absorb water. A minimum of 28 days cured is required on all concrete. Before starting flooring work, test existing concrete slab for efflorescence, moisture, and hydrostatic pressure.

MOISTURE

All concrete should be tested for moisture before applying a seamless coating. Water vapour transmission upwards through on-grade concrete slabs may result in loosening of epoxy floors or improper curing of epoxy materials.

PREPARATION

Pre-cut and clean all cracks and joints with a concrete diamond blade. Prepare concrete to a profile finish to ensure good bonding. You may mechanically profile by grinding, shot blasting, scarifying, or water blasting. Methods may vary according to the thickness of the coating to be applied and the condition and hardness of the concrete. Other factors include the forecasted use of the surface and the environment in which it is to be installed. When preparing the surface use caution when shot blasting around pools, scarifying too aggressively, leaving grinding marks or grinding too smooth. Ensure that concrete is very level, any high or low spots will affect the final look of the Stucco Delight floor.

Stucco Italiano



APPLICATION

Primer:

Primer to be used must be Stucco Epoxy Waterborne Primer. Due to the transparency of the Stucco Delight, the primer must be pigmented. For best results, choose a primer similar in colour to the Stucco Delight colour being used.

Decant primer one container of part A and one container part B as supplied, in a clean suitable container and mix together for 3-4 minutes. Immediately apply using a brush and roller at a rate of 7m² to 10m² per litre.

Make sure the substrate is completely sealed. A second coat of primer may be needed to completely seal the concrete to reduce the possibility of bubbling.

Allow primer to cure a minimum of 18 hours and maximum of 24 hours before applying Stucco Delight.

Stucco Delight:

Decant Part B into the container containing part A and mix thoroughly for 3minutes. Decant the mixed contents into another clean container and mix for another 2 minutes. Immediately apply the mixed product using a sponge roller or a trowel, depending on the desired effect at a rate of 1m² per litre.

To avoid bubbles it is best to apply Stucco Delight when temperature is dropping and in an area that is not in direct sunlight.

MAINTENANCE

Interior Floors can be dust mopped daily or mopped using a low pH cleaner.

HEALTH PRECAUTIONS

Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs. Avoid breathing vapours, it is strongly recommended that respirators are worn.

Prolonged or repeated skin contact can cause slight skin irritation. All epoxies have the potential of causing skin irritations or allergic reactions. Be careful not to get on skin, clothes or in eyes. Gloves are strongly recommended.

If splashed in the eye, flush with warm water and contact a physician if blurring persists.

MANUFACTURED BY

Stucco Italiano
25 Industria Rd
Brackenfell
Tel: 021-982 0006
Fax: 021-982 3796
E-mail: info@stuccoitaliano.co.za
www.stuccoitaliano.co.za