

Stucco Italiano



STUCCO EXTERIOR WALL SEALER

DESCRIPTION

STUCCO EXTERIOR WALL SEALER is a single phase, clear acrylic sealer for exterior surfaces. It is applied after STUCCO HARDENER is applied and cured onto STUCCO AQUAGUARD BRUSH ON and STUCCO AQUAGUARD WALL PLASTER.

PURPOSE

STUCCO EXTERIOR WALL SEALER is applied to STUCCO AQUAGUARD BRUSH ON and STUCCO AQUAGUARD WALL PLASTER to protect the wall from dirt and weathering.

APPLICATION

Necessities

STUCCO EXTERIOR WALL SEALER in it's packaging, roller tray, roller, brush, spray equipment, masking tape, drop sheets and cleaning thinners.

Preparation

Cement and concrete surfaces must be dry, clean and free from any dust, saline deposits, greasiness or any materials that can prevent binding.

Saline deposits and greasiness can be washed off with washing soda.

Stir the contents of the tin before use, but do not shake.

Application

Cover windows, doors and light fittings with masking tape and paper and put drop sheets on floor.

First apply a single layer of STUCCO COLOUR FASTENER using a roller or brush as per STUCCO COLOUR FASTENER data sheet and allow the STUCCO COLOUR FASTENER to dry overnight.

Apply using a brush, a roller or spray equipment and allow to dry for minimum of 2 hours before applying second coat.

Do not apply if rain is eminent within 8 hours.

TECHNICAL DATA

Type: Acrylic based
Drying time: 2 hours @ 23°C
Shelf life: 12 months
Coverage: ± 5m² per litre (two coats)
Packaging: 1L and 5L tins
Storage: Store in a cool, dry place away from heat and open flames

WARNING

STUCCO EXTERIOR WALL SEALER is flammable.
Do not ingest. Keep away from children and pets. Do not empty into drains.

Stucco Italiano



PRECAUTIONS

Wear rubber gloves. In the event of contact with eyes or skin, rinse thoroughly with cold water.
If irritation or discomfort occurs, seek medical advice.

MANUFACTURED BY

Stucco Italiano
25 Industria Rd
Brackenfell
Tel: 021- 982 0006
Fax: 021-982 3796
E-mail: info@stuccoitaliano.co.za
www.stuccoitaliano.co.za